



# *Delivering The Difference*

**Model 930**



**LANDOLL 930**



## *Traveling Tail*

# Standard & Optional Equipment / Features - Model 930 Traveling Tail

S=Standard O=Optional

MODEL 930	35 Ton	70,000#
<b>MAIN FRAME</b>		
- Fabricated 80,000 # PSI		S
- Four Beam Design		S
- Capacity-70,000# Distributed / 50,000# Concentrated in 10'		S
<b>KINGPIN SETTING</b>		
- 18" Setting		S
- 86" Swing Clearance		S
<b>CROSSMEMBERS</b>		
- 4" Jr. I-Beam on 12" Centers		S
<b>DECK &amp; FEATURES</b>		
- 102" Wide		S
- 90 Degree Slope Drop		S
- 37-1/4" Deck Height (Loaded)		S
- 1 3/8" Nominal Apitong (Lower Deck)		S
- 20" Loaded Ground Clearance		S
<b>TAIL</b>		
- 12 Ft. (15° Load Angle)		S
Model 930-45-12 (Lower Deck Length 34')		S
Model 930-48-12 (Lower Deck Length 37')		S
- 15 Ft. (11° Load Angle)		S
Model 930-48-15 (Lower Deck Length 37')		S
Model 930-51-15 (Lower Deck Length 40')		S
- Six Flush Double Key Hole Side Chain Slots		S
- Flat Approach Plate w/Six Gotcha Tie Downs at Rear of Plate		S
- Apitong Wood Covered		S
- Lifting Capacity-24,000#		S
<b>WINCHES &amp; ACCESSORIES</b>		
- Upper Deck 12,000# Worm Gear w/85' Cable w/Slope Roller		S
- Slope Mtd Winch Optional - 12,000#, 15,000#, 20,000#		O
<b>TIE DOWNS / CHAIN GOTCHAS</b>		
- Double Key Hole Chain Slots/Gotchass on 24" Centers		S
<b>TOOL BOX</b>		
- Street Side Under Lower Deck (42"W x 28"D x 9"H)		S
<b>SLOPE RAMP</b>		
- 5 Ft. Aluminum Ramps (Portable)		O
- Upper Deck Ramp (Air Operated)		O
- Landoll Traction Ramps (Steel) (Portable)		O
<b>LIFT CYLINDER</b>		
- Combination Tilt/Travel Cylinder		S

MODEL 930	35 Ton	70,000#
<b>AXLES</b>		
- (2) 25,000# Tandem Dual Tire, Oil Bath Bearings		S
<b>SUSPENSION</b>		
- Neway Air Ride RLU228 22,500# Capacity with Manual Dump Valve		S
<b>BRAKES</b>		
- Automatic Slack Adjusters		S
- 12.25 x 7.5 Full Air w/spring Brakes One Axle		S
- ABS, Rockwell 4S2M		S
<b>OIL SEAL HUBS</b>		
- Internal Mated Assembly		S
<b>TIRES/WHEELS</b>		
- 10R 17.5 Goodyear LRH		S
- Hub Pilot/Steel Outboard Brake Drum		S
<b>RIMS</b>		
- 17.5 x 6.75 Tubeless		S
<b>HYDRAULIC POWER SOURCE</b>		
- Truck Mtd Air Shift PTO , Pump and Hyd Res		O
- Self Contained Hyd System Under Slope Mtd		O
<b>HYDRAULIC HOOK UP</b>		
- Hydraulic Quick Couplers 2500 PSI/17 GPM		S
<b>AIR/ELECTRICAL CONNECTION</b>		
- 7 Way Receptacle (Electrical)		S
<b>LIGHTS</b>		
- 3 Light Tail System, Sealed Beam Grommet Mounted with Sealed Wiring Harness, Center Mounted Turn Signal		S
<b>FINISH/COLOR</b>		
- Steel Grit Shot Blast to Bright Metal		S
- Epoxy Primer		S
- Acrylic Urethane		S
White, Black, Yellow, Blue, Red, Green		S
<b>WEIGHT</b>		
- 48' - 16,300#		S
SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE. MORE OPTIONS AVAILABLE - CONSULT FACTORY PICTURES MAY SHOW OPTIONAL EQUIPMENT.		



Delivering The Difference! Visit us at [www.landoll.com](http://www.landoll.com)



Call 1-800-428-5655 for your BEST hauling solutions!

1900 North Street • Marysville, KS 66508 • Ph. 785-562-5381 • FAX 785-562-4893

Remember: Quality is Always a Bargain!

930T -1000