



Specifications:

LENGTH:	36 FT. to 42 FT.
WIDTH:	96 INCHES
HEIGHT:	68" SIDES, 14 GAUGE
SUSPENSION:	HUTCH 9700 48,000 LB. TANDEM AXLE
AXLES:	ROCKWELL 25,000 LB. TANDEM AXLE
ABS BRAKES:	ABS ON ONE AXLE 2 SENSORS AND MODULATOR VALVE
WHEELS:	8.25" X 24.5"
TIRES:	DUNLOP SP-160 11R X 24.5" RADIAL TIRES
TOP RAIL:	4" X 3" X 3/16" TUBE
BOTTOM RAIL:	4" X 3" X 3/16" TUBE
BUMPER:	ICC STANDARD
KING PIN:	18" FOR STRAIGHT AND SLOPE END
COUPLER HEIGHT:	49"
LADDERS:	FRONT AND REAR WALK PLATFORM
TOP:	OPEN TOP
TARP:	SHUR LOK ROLL OVER TARP
HOPPERS:	14 GAUGE
DOORS:	24" X 24" OPENING
LANDING GEAR:	TWO SPEED LANDING GEAR
LIGHTING:	GROTE BLUE SEAL DOT AND ICC APPROVED, SEALED, RUBBER MOUNT WITH 7-WAY PLUG
MUD FLAPS:	ANTI-SAIL
PAINT:	SANDBLAST, PRIMER AND PAINT WITH CARBOLINE PAINT COLOR WHITE
OPTIONS:	4 SENSOR/2 MODULATOR ABS; 30" X 30" DOORS; VIBRATOR (2 BRACKETS); SIDE CHUTES; 2 SPEED DOORS